

CHAINS

A 30" fir bears N. 85° E. 60.2 ft., scribed 1/4 S. B.T.  
(Since broken off about 6 ft. above the ground.)

At the corner to sections 3-2-10-11 we found a 56" scribed fir snag and 3 rotten stumps in proper position for the other bearing trees. For the section corner we set a 2" x 48" galv. iron pipe with brass cap on which is stamped a cross and the numbers 3-2-10-11 and, circumferentially, SEC. COR. T. 3 N. R. 6 W.W.M. - O.S.H.D. We also set a 4" x 4" white guard post stenciled SEC. COR. on 2 faces in black, and marked 4 new bearing trees, as follows:

An 8" fir bears N. 40° E. 31.6 ft., scribed T.3N.R.6W. S.2B.T.

An 8" fir bears N. 65° W. 20.1 ft. scribed T.3N.R.6W. S.3B.T.

A 10" fir bears S. 30° W. 29.1 ft., scribed T.3N.R.6W. S.10B.T.

A 12" fir bears S. 60° E. 37.0 ft., scribed T.3N.R.6W. S.11B.T.

Thence N. 0° 42' W. on a true line between sections 3 and 2.

Set a 3/4" x 30" iron pin for the South 1/16 corner on the line between sections 3 and 2, with a 4" x 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.

The quarter corner between sections 3 and 2, previously described.

Thence N. 0° 16' W., continuing on a true line between sections 3 and 2.

Centerline of the Wolf Creek highway at Sta 1229+70.5 P.O.T.

Set 3/4" x 30" iron pin for the North 1/16 corner on the line between sections 3 and 2, with a 4" x 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.

The corner to sections 34-35-3-2, on the line between townships 3 and 4 North, previously described.

From the corner to sections 2-1-11-12, we ran Westerly by traverse to the quarter corner between sections 2 and 11, where we found the scribed stump of one bearing tree. For the quarter corner we set a 2" x 48" galv. iron pipe with brass cap on which is stamped a line with short cross mark and the numbers 2 and 11 and, circumferentially, 1/4 COR. T. 3 N. R. 6 W.W.M. - O.S.H.D. We also set a 4" x 4" white guard post stenciled 1/4 SEC. COR. on 2 faces in black, and marked 2 bearing trees, as follows:

A 10" hemlock bears S. 30° E. 18.6 ft., scribed 1/4S. B.T.  
An 18" hemlock bears N. 2° W. 19.8 ft., scribed 1/4S. B.T.

This quarter corner is at a point 2643.2 ft. S. 89° 26 1/2' W. from the corner to sections 2-1-11-12, and also, 2635.7 ft. N. 89° 37' E. from the corner to sections 3-2-10-11.

Thence we ran N. 0° 42 1/2' W. thru the center of section 2.

Set a 3/4" x 30" iron pin for the South 1/16 corner on the N. & S. centerline of the section, with a 4" x 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H.D. PROP. COR. on other 2 faces in black.

Set temporary center of section.

The 1/4 corner between sections 35 and 2 on Twp. line, previously described

Returning to the quarter corner between sections 2 and 1, we ran

SEC. COR.  
3, 2, 10, 11  
3, N. 6.  
S.W. of 2

1/16 COR.  
2, 3-3, N. 6.  
S. on W. BDRY  
of 2

1/16-COR.  
2, 3-3, N. 6.  
N. on W. BDRY  
of 2

1/4 COR.  
2, 11-3, N. 6.

1/4 COR. S. BDRY  
of 2

1/4 COR.  
2, 11-3, N. 6.

1/16 COR.  
2-3, N. 6.  
S. on W. of 2

13+26.7

26+53.5

27+98.0

39+73.1

47+81.6

13+27.6

26+55.1

47+49.7

Book I