

24

	CHAINS	
		<p>A 20" fir bears S. 75° W. 61.4 ft., scribed T. 3 N. R. 6 W. S.9 B.T. This tree has old deep blaze on East near base and has been chopped into deeply on the North.</p> <p>A 10" fir bears N. 55° W. 66.1 ft., scribed T. 3 N. R. 6 W. S.4 B.T.</p> <p>A 4" fir bears N. 20° E. 19.7 ft., scribed T. 3 N. R. 6 W. S.3 B.T.</p> <p>A 4" fir bears S. 65° E. 27.7 ft., scribed T. 3 N. R. 6 W. S.10 B.T.</p> <p>Thence we ran N. 0° 26' W. on a true line between sections 4 and 3.</p> <p>For the 1/4 corner on the line between sections 4 and 3, we set a 2" x 48" galv. iron pipe with brass cap on which is stamped a line with short cross mark and the numbers 4 and 3 and, circumferentially, 1/4 COR. T. 3 N. R. 6 W.W.M. - O.S.H.D. We also set a 4" x 4" white guard post stenciled 1/4 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black. No live trees available for bearing trees.</p> <p>Centerline of the Wolf Creek highway at Sta. 1170+83.5 P.O.C.</p> <p>The corner to sections 33-34-4-3 on the Twp. line, previously described.</p> <p>Returning to the corner to sections 4-3-9-10, we ran Easterly by traverse to the quarter corner between sections 3 and 10. At a point 2660.8 ft. S. 89° 26' E. from the section corner, we found a heap of shattered stone with 1/4 cut in the face of one piece. We also found a dead 30" fir S. 24° 45' W. 15.2 ft. scribed 1/4 S. B.T., and a rotten stump N. 77° E. 15 ft. For the quarter corner we set a 2" x 48" galv. iron pipe with a brass cap on which is stamped a line with short cross mark and the numbers 3 and 10 and, circumferentially, 1/4 SEC. COR. T. 3 N. R. 6 W.W.M. - O.S.H.D. We piled the fragments of stone around the pipe and set a 4" x 4" white guard post stenciled 1/4 SEC. COR. on 2 faces in black. No live trees available for bearing trees.</p> <p>This corner lies 2649.3 ft. N. 89° 00' W. from the corner to sections 3-2-10 and 11.</p> <p>Thence we ran N. 0° 13' W. thru the center of section 3.</p> <p>Set 3/4" x 30" iron pin for the South 1/16 corner on the N. &amp; S. centerline of the section, with 4" x 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.</p> <p>The temporary center of the section.</p> <p>3/4" x 30" iron pin for the North 1/16 corner on the N.&amp;S. centerline of section 3, with 4" x 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.</p> <p>The 1/4 corner between sections 34 and 3, previously described.</p> <p>Returning to the quarter corner between sections 4 and 3, we ran</p> <p>S. 89° 11 1/2' E. thru the center of section 3.</p> <p>3/4" x 30" iron pin for the West 1/16 corner on the E.&amp;W. centerline of section 3, with 4" x 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.</p> <p>Intersect the N.&amp;S. centerline of the section at Sta. 26+44.6, the temporary center of section. For the center of section we place a concrete pedestal 12" square at top, 18" square at bottom and 36" high, set 30 inches in the ground, with a 2 1/2" brass disc on which is stamped a circle and the number 3 and, circumferentially, CEN. SEC. T. 3 N. R. 6 W.W.M. - O.S.H.D.</p>
26+55.6	<p>SEE pg. 22 -</p> <p>1/4 COR. 34-3N6</p> <p>1/4 COR. ON W BDRY 3</p>	
41+53.1		
47+25.0		
13+22.3	<p>1/4-COR. 310-3N6</p> <p>1/4 COR. S. BDRY 3 - 3N6</p>	
26+44.6		
39+55.4		
47+22.9		
13+35.7	<p>1/16-COR. 3-3N6</p>	
26+71.3	<p>CEN.</p> <p>1/4 COR. INTERSECTION 3-3N6</p>	

Book I