

26+74.5
47+90.3

26+30.3

52+76.3

CHAINS
1/4 COR.
4-3 N. 6.

1/4 COR.
INTERIOR
4-3 N. 6.

A 6" fir bears S. 55° W. 7.4 ft., scribed 1/4 S.B.T.
A 12" fir bears N. 30° E. 18.4 ft., scribed 1/4 S.B.T.

Thence we ran N. 0° 14' W. thru the center of section 4.

Set temporary center of section.
The 1/4 corner on the North boundary of the section.

Returning to the 1/4 corner on the East boundary of the section, we ran,

S. 89° 15 1/2' W. thru the center of section 4.

Intersect the N.&S. centerline of the section at Sta. 26+74.5, the temporary center of section. For the center of section 4, we set a 2" x 48" galv. iron pipe with the brass cap on which is stamped a circle and the number 4 and, circumferentially, CEN. SEC. T. 3 N. R. 6 W.W.M. - O.S.H.D. We set a 4"x4" white guard post stenciled CENTER SEC. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black. No live trees available for bearing trees.

The 1/4 corner on the West boundary of the section.

Registered Professional
Engineer

1960

'A. V. Benedict'

Dated at Forest Grove, Oregon.
January 19, 1943.

Oregon
May 5, 1939

A. V. Benedict