

~~CHAINS~~
Feet

SURVEY BY OREGON STATE BOARD OF FORESTRY OF THE TOWNSHIP LINE
BETWEEN SECTIONS 1 & 12 T1N R6W AND SECTIONS 6 & 7 T1N R5W

RETRACEMENT

Beginning at the corner of Twps 1 & 2 N, Rges 5 & 6 W WM,
determined by a cedar stump and an iron pipe $1\frac{1}{2}$ inches in
diameter with an Oregon State Board of Forestry bronze cap
stamped T2N R6W R5W S36, S31, S1, S6 T1N 1949, 1557.

Starting with a compass bearing, variation 22° E, using a
K & E Light Mtn Transit
I run South on a random line between Sections 1 & 6 T1N
Rges 5 & 6 W.

- 2640 Set temp. stake, find no evidence of $1/4$ corner.
- 3370.5 Logging road running NW & SE. Set stake on S side of road.
- 4103.5 Stream, course $S 70^{\circ} W$.
- 5280 Set temp. stake. Find no evidence of cor. to Secs. 1, 12,
6 & 7.
Continue South bet. Sections 12 & 7.
Beginning new measurement.
- 179 Spring branch, course West.
- 265 Logging road.
- 1902 Stream, course East.
- 2640 Set temp. stake, find no evidence of $1/4$ corner.
- 2681 Stream, course $S 10^{\circ} E$.
- 3512 Road.
- 4322 Stream, course $S 80^{\circ} E$.
- 5280 The cor. of Sections 7, 18, 12, 13 bears $N 80^{\circ} 23' E$
a distance of 40.1 feet.
The corner determined by an iron pipe $1\frac{1}{4}$ inches in diameter
and a stone 6" x 6" x 5" above ground with 4 notches on the
SW face and 2 notches on the NE face.
