

~~XX~~  
FEET

Adjustment of temporary stakes to true line position by single proportionate measurement and establishment of monuments.

Relative to the compass bearing of the random line the true line bears S 0°13' E a distance of 10553.4 ft.

2638.3

Point for 1/4 corner between Secs. 1 & 6.

Adjustment from temp. stake 2640 - North 1.7 ft. East 9.8 ft.

Set an iron pipe 1 1/2 inches in diam., 3 ft. long, filled

1/4 COR.

1,6 -

1. N. 5 + 6. W.

with charcoal with an Oregon State Board of Forestry bronze

cap stamped 1/4, S1, S6, 1949 199

from which:

A cedar snag 12 inches in diam. bears S 03° W  
a distance 20.8 feet. Scribed, 1/4 S6 199.

A metal location poster on this snag is marked  
S 1 & 6 T1N R 5 & 6 W, 1/4 cor., 20.8 ft. N 3° E.

3362.3

Set a 4" x 4" x 4" cedar post on true line at side of road

with a metal location poster marked S 1 & 6 T1N R 5 & 6 W

1/4 cor. 724 ft. North.

5276.7

Point for sec. cor. to Sections 1, 12, 6 & 7.

Adjustment from temp. stake 5280. North 3.3 ft. East 19.7 ft.

Set an iron pipe 1 1/2 inches in diameter, 3 ft. long, filled

with charcoal, with an Oregon State Board of Forestry bronze

cap stamped T1N S1, S36, S12, S7 R6W R5W, 1949, 199.

from which:

A fir snag 32" in diam. brs. N 15° E a distance of 28.0 ft.  
Scribed T1N R5W S6 199.

A metal location poster on same snag marked  
Sec. 6 T1N R5W Sec. Cor. 28 ft. S 15° W.

Continuing S 0°13' E on same line, bet. Sections 7 & 12.

Beginning new measurement.

2638.3

Point for 1/4 corner between Secs. 7 & 12.

Adjustment from temp. stake 2640 North 5.0 ft., East 29.5 ft.

Book I