

Cour Surveyor's Record, Tillamook Cour Oregon

97

7418 Sec cor bet 7,8 T1S R10W	CHAINS found old 24" hem badly rotted made 6" hem S63W, 27 ft and a 60" spruce marks chopped out. Found 2x2 white lot stake and old hem stake cor lies 5 ft east of small creek running north.
Sec cor 1,6,7,12 T3N R9-10W	In the presence of W. E. Anderson and Francis L. Smith, Dec'51 Found 1" iron pipe in road NW cor of cheese factory bears S76-15E, 206.4 ft Lead plug in end of curb on up stream side of bridge, S86W, 181.1 ft. Remarked 24" alder in bark, S5W, 43.8 ft. old BT. In the presence of W. E. Anderson and Francis L. Smith, Jan 1952
Quick & Trask D.L. T1S R9W	2" Iron Pipe off Shoulder Lead plugs in cor of bridge N.W. Cor. Trask D.L.C. Z65 1010
	QUICK D.L.C. PUD Pole 22 ft 1/2" I.P. by Fence Post 22 ft PUD Pole 31.0 PUD Guy 6 ft
Sec cor 30,29,19, 20 T4S R10W	Corner is 1 1/4" iron pipe 2 ft long with top drove flush with ground level and is in fence line. A 36" spruce tree bears south 19.0 ft. In the presence of W. E. Anderson and Francis L. Smith,
1/4 cor bet sec 36,1 T1-2S R10W	Set 2" I.P. From old BT marks are now burnt off but were plain in 1941. New BT's;
Sec cor. 3,2,34,35 T1-2S R9W	4" hem N39E, 54 ft 18" spruce N57W 43.2 ft Cor is on high ground and on south side of Trask River In the presence of W. E. Anderson and Francis L. Smith April 1952
1/4 cor cen sec sec 3 T2S R9W	Set 1 1/4" iron pipe flush with ground from which a 16" fir bears N42W, 45.7 ft 12" spruce bears N62E, 81.2 ft In the presence of W. E. Anderson and Francis L. Smith April 1952
Book I 97 1/16 cor	Set 1 1/4" iron pipe flush with ground from which a 18" alder bears N13W, 53.8 ft 12" alder bears N72E, 60.0 ft In the presence of W. E. Anderson and Francis L. Smith April 1952