

CHAINS

RESTORED CORNER FOR OREGON STATE BOARD OF FORESTRY

Section corner common to Sections 11, 12, 13 and 14,
Township 3 North, Range 7 West, W.M., Tillamook
County, Oregon.

ORIGINAL

Stone 20" x 12" x 5" now in place 15" in ground with 4
notches on South edge and Innotch on East edge from
which a:

- 48" Fir bears N60°E 38 lks.; now 50" stump, face
not cut out.
- 15" Hemlock bears S34°E 52 lks.; now 20" stub par-
tially uprooted, BT scribes visible, scribes
R7W S13 on piece on ground.
- 70" Fir bears S37°W 10 lks.; now 72" stump, no
face or scribes remaining.
- 12" Hemlock bears N59°W 61 lks.; now missing,
point falls in skid road.

RESTORED

Erected mound of rock 3' x 4' x 10" around original
stone, from which a:

- 60" Fir stump bears S75°E 56.4 ft.; scribed T3N
R7W S13 BT.
- 55" Fir stump bears N37°E 41.8 ft.; scribed T3N R7W S1
S12 BT.
- 59" Fir stump bears S14W 55.6 ft.; scribed T3N
R7W S14 BT RE 2311.
- 58" Fir stump bears N2°W 50.2 ft.; scribed T3N
R7W S11 BT.

Oregon State Board of Forestry metal location poster on ori-
ginal 70" Fir BT.
4" x 3" x 72" white Cedar post 1.5 ft. SE of pipe.
Also poster on 60" Fir stump, BT.

Dated March 24, 1954.

Restored by Richard Morris under my direction.
Richard Morris, Compassman



Present and witnessed by Robert Cowan, Lloyd Geraths, Alan Ramage.