## **OREGON STATE HIGHWAY COMMISSION**

INTER-DEPARTMENT CORRESPONDENCE

Subject:

To:

T. 2. N. R. 6. W.

Quarter corner between 33-34 T. 2. N. R. 6. W.

Found squared stake. Yew tree blown down; 24" fir now about 36" stump with origional scribing plainly visible. Set 33" piece of inch and quarter iron pipe with I" pipe inside 24" in ground. Boat spike in spring board notch of 40" fir stump S. 26° W. I2.5

Section corner 27-28-33-34 T. 2. N. R. 6. W.
Origional Hemlock N. I9° W. 38 links, only tree standing.
Can read T. 2. N. 6. W. rest is rotted and burnt away. Fir
is down and half buried. Other trees have dozed out of place.
Set 5' piece of 2I/2" pipe 30" in ground. I/2" dowel in top
of 30" fir stump bears S. 26° E. 39.6 Boat spike in top of
48" fir stump bears S. 84° 30' E. 24.0

Aug. I9-42

Section corner 25-26-35-36 T. 2. N. R. 6. W. Found squared stake set from Yew stump; only remains of origional bearing trees. Set 33" piece of I" iron pipe inside of an inch and a quarter pipe 27" in ground. 4x4" cedar stake. No suitable trees for witness trees.

Book I