

TELLAMOOK COUNTY

numbers 34 and 3 and, circumferentially, 1/4 COR. TPS.3&4 N.R.6 W.W.M. O.S.H.D. This is 2624.2 ft. S.89° 45'W. of the section corner. We also set a 4"X 4" white guard post stenciled 1/4 SEC.COR. on 2 faces and O.S.H. PROP.COR. on other 2 faces in black. No live trees available for bearing trees.

Continuing Westerly by traverse between sections 34 and 3, we found 2 dead bearing trees, properly scribed, and the stump of a third, for the corner to sections 33-34-4-3. At a point 2678.8 ft. N.89° 25'W. from the quarter corner between sections 34 and 3, we place a concrete pedestal 12" square at top, 18" square at bottom and 36" high, set 30 inches in the ground, with a 2 1/2" brass disc on which is stamped a cross and the numbers 33-34-4-3 and, circumferentially, SEC.COR.TPS.3&4 N.R.6 W.W.M. - O.S.H.D. We also set a 4"X 4" white guard post stenciled SEC.COR. on 2 faces and O.S.H.PROP.COR. on other 2 faces in black. No live trees available for bearing trees.

Thence Westerly by traverse along the highway, with spurs to the 1/4 corner between sections 33 and 4 and to the corner to sections 32-33-5-4, after which we return to the corner to sections 33-34-4-3 and run thence,

N.89° 46'W. on a true line between sections 33 and 4.

7+78.4
13+0800

Centerline of the Wolf Creek highway at Sta. 1161+14.3 P.O.C. 3/4"X 30" iron pin for the East 1/16 corner on the line between sections 33 and 4, with a 4"X 4" white guard post stenciled 1/16 SEC.COR. on 2 faces in black.

26+16.1

The point established for the quarter corner between sections 33 and 4. We found a 16" hemlock snag scribed for the S.E. bearing tree but no trace of the other one. For the quarter corner we set a 2"X 48" galv. iron pipe with brass cap on which is stamped a line with short cross mark and the numbers 33 and 4 and, circumferentially, 1/4 COR.TPS.3&4 N.R.6 W.W.M. - O.S.H.D. We also set a 4"X 4" white guard post stenciled 1/4 SEC.COR on 2 faces and O.S.H.PROP.COR. on other 2 faces in black. No live trees available for bearing trees.

39+33.1

Thence we ran N89° 57'W. continuing on the true line between sections 33 and 4.

3/4"X 30" iron pin for the West 1/16 corner on the line between sections 33 and 4, with a 4"X 4" white guard post stenciled 1/16 SEC.COR. on 2 faces and O.S.H.PROP.COR. on other 2 faces in black.

52+50.1

The corner to sections 32-33-5-4, where we found 3 dead bearing trees, scribed, from which we set a 2"X 48" galv. iron pipe with brass cap on which is stamped a cross and the numbers 32-33-5-4 and, circumferentially, SEC.COR. TPS.3&4 N.R.6 W.W.M. - O.S.H.D. We also set a 4"X 4" white guard post stenciled SEC.COR. on 2 faces in black. No live trees available for bearing trees.

Thence we ran Westerly by traverse to the quarter corner between sections 32 and 5, where we found a 20" hemlock snag scribed for the original quarter corner and 2 dead bearing trees. The quarter corner is 2633.2 ft. S.89° 40 1/2'W. of the section corner. At a point 3.0 ft. EAST of the true corner we set a 2"X 48" galv. iron pipe for a witness corner, with brass cap on which is stamped a line with short cross mark and the numbers 32 and 5 and, circumferentially, 1/4 COR.W.C.TPS.3&4 N.R.6 W.W.M. - O.S.H.D. We also set a 4"X 4" white guard post stenciled 1/4 SEC.COR. on 2 faces in black. No live trees available for bearing trees.

Book I

Book I