

1/10/41

TILLAMOOK COUNTY

Returning to the corner to sections 4-3-9-10, we ran Westerly by traverse to the quarter corner between sections 4 and 9.

At a point 2633.9 ft. S. 88° 50' W. of the section corner, we found a stone with 1/4 cut into the North face, with a 36" green fir N. 4° W. 101.0 ft., and a 36" larch snag S. 48° W. 75 ft. Leaving the stone undisturbed, we set a 2"X 48" galv. iron pipe at a point 0.4 ft. West and 0.1 ft. North of the cross on the stone. The pipe has a brass cap on which is stamped a line with short cross mark and the numbers 4 and 9 and, circumferentially, 1/4 COR. T. 3 N. R. 6 W.W.M. - O.S.H.D. We set a 4"X 4" white guard post stenciled 1/4 SEC. COR. on 2 faces in black, and marked two new bearing trees, as follows:

- A 6" fir bears S. 55° W. 7.4 ft., scribed 1/4 S.B.T.
- A 12" fir bears N. 30° E. 18.4 ft., scribed 1/4 S. B.T.

Thence we ran N. 0° 14' W. thru the center of section 4.

26+74.5  
47+90.3

Set temporary center of section.  
The 1/4 corner on the North boundary of the section.

Returning to the 1/4 corner on the East boundary of the section, we ran,


S. 89° 15 1/2' W. thru the center of ~~the~~ section.4.

26+30.3

Intersect the N.& S. centerline of the section at Sta. 26+74.5, the temporary center of section. For the center of section 4, we set a 2"X 48" galv. iron pipe with brass cap on which is stamped a circle and the number 4 and, circumferentially, CLN. SEC. T. 3 N. R. 6 W.W.M. - O.S.H.D. We set a 4"X 4" white guard post stenciled CENTER SEC. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black. No live trees available for bearing trees.

52+76.3

The 1/4 corner on the West boundary of the section.



Dated at Forest Grove, Oregon.  
January 19, 1943.