

CHAINS

RESTORED CORNER FOR OREGON STATE BOARD OF FORESTRY

Section corner common to Sections 7, 12, 13, and 18,  
T1S, R6 & 7, W.M, Tillamook County, Oregon

ORIGINAL

Post, now missing from which a:

- 10" Hem. bears S50<sup>1</sup>/<sub>2</sub>°W 31 lks.; now 11" uproot, roots in place, scribes BT visible, upper face burnt out.
- 30" Fir bears S24<sup>1</sup>/<sub>2</sub>°E 44 lks.; now 30" snag, scribes S 18 visible, rest unexposed.
- 22" Hem. bears N52°E 9 lks.; now 20" stub 6 ft. high, scribes T1 BT visible, rest burnt out.
- 30" Hem. bears N18°W 9 lks.; now 29" stub 15 ft. high, scribe marks visible in edge of burnt out face.

Original notes call for using variation 14°15', but the only variation that checked for bearings and distances was 8°E.

RESTORED

Set 1<sup>1</sup>/<sub>2</sub>" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY T1S R7W R6W S12 S7 S13 S18 1954 RE2311," 34 inches in ground, in mound of stone, and from which a:

- 47" Fir snag bears N6°W 35.8 ft.; scribed T1S R7W S12 BT RE2311.
- 66" Fir snag bears S9E 47.3 ft.; scribed T1S R6W S18 BT
- 61" Fir snag bears S9°W 153.5 ft.; scribed T1S R7W S13 BT
- 17" Cedar snag bears N72°E 59.0 ft.; scribed T1S R6W S7 BT.

Oregon State Board of Forestry metal location poster on 47" Fir Snag BT. Set 4" x 4" x 84" White Cedar post 2 ft. SW of pipe.

Dated December 31, 1954

Restored by Richard Morris under my direction  
Richard Morris, Engr. Aide.



Present and witnessed by Lloyd Geraths  
Claude Wiekkel  
Forrest Logan