

County Surveyor's Record, Tillamook County, Oregon

241

T 5 S, R 9 W.

Rewitnessed Corners.

Mervin Whitmore, U.S. Forest Service

<p>10/11/1954 Sec. Cor. 21 22 28 27</p>	<p>Old fir limb post scribed YAMHILL CO. on E. side, scribing on W side rotted off, from which A 48" dead fir snag bears S 27°W 41 feet slope dist. mkd. TILLAMOOK CO BT (old BT). A 36" fir bears N 47°W 49 feet slope dist. mkd. T5SR9WS22BT (new BT) A 36" fir bears N 56°E 12½ ft. slope dist. mkd. T5SR9WS22BT (new BT) This corner sets about 100 feet up from the foot of a steep S. slope. In the presence of M.L. Dawson. June 22, 1954.</p>	
<p>¼ SecCor 29 32</p>	<p>Set a 1¼" pipe for ¼ sec cor to Secs. 29 & 32 from which A 54" dead fir snag bears S 67°E 58 ft. mkd ¼SBT (old BT) An 18" fir bears S 11°E 9 ft. scribed in bark ¼S32BT (new BT) A 28" fir bears N 42°W 21.5 ft. mkd. ¼S29 BT (new BT) In the presence of Willis Horner & Ralph Lippert. April 28, 1955.</p>	
<p>¼ Sec.Cor. 30 29</p>	<p>Set a 1¼" pipe from which A 54" dead fir snag bears S 61°E 60 lks. mkd. ¼S (old BT) A 22" fir bears N 8°W 53.7 feet mkd. ¼S30BT (new BT) A 24" alder bears N 25°E 4.5 feet mkd. ¼S29 BT, scribed in bark (new BT) In the presence of John Carlich. May 6, 1955.</p>	
<p>¼ Sec.Cor. 29 28</p>	<p>Set a 1¼" pipe from which A 48" dead fir snag bears N 74°E 160 lks. mkd. ¼SBT (old BT) A 54" dead fir snag bears S 90°W 59 lks. all marks rotted off (old BT) A 26" fir bears N 81°E 28.7 feet mkd. ¼S28BT (new BT) A 24" spruce bears N 53°W 15.5 feet mkd. ¼S29BT (new BT) In the presence of Martin Chaffee. May 17, 1955</p>	
<p>Book I 241</p>		<p>241</p>