	CHAINS	
· Lucoa	36.95	$\frac{1}{4}$ -section corner of Sections 6 and 7. From this corner:
4000		Dead Fir 16" diameter (original B.T.) with the original scribe marks clearly visible bears North $67\frac{1}{2}^{\circ}$ West 13 links distant. There is no trace of the yew or stone that are called in the original survey notes.
		Begin at the corner of Sections 6 - 7 of Township 1 South, Range 6 West, W. M. and 1 - 12 of Township 1 South, Range 7 West, W. M. and run South 10 43' East. Variation 220 East.
14 CUR.	49.035	$\frac{1}{4}$ -corner of Sections 7 and 12.
12 17		
CEN. 74 SE	c.7	Begin at the $\frac{1}{4}$ -corner of Sections 7 and 12 and run North 84° 51' East on the true center line of Section 7 to the $\frac{1}{4}$ -corner between Sections 7 and 8. Begin also at the $\frac{1}{4}$ -corner between Sections 6 and 7 and run South 4° West on the true center-line of Section 7 to the $\frac{1}{4}$ -corner of Sections 7 and 18. At the true intersection of the centerlines of Section 7, set an iron pipe $1\frac{1}{2}$ " x 30" and raise a mound of stones for the center corner of Section 7, Township 1 South, Range 6 West, W. M. From this corner:
	·	Dead Fir 64 " diameter bears North 63° West $16\frac{1}{2}$ links distant.
		Dead Fir 60" diameter bears North 83° East 47 links distant.
		No trees or bearing objects available South of the corner.
		I have caused this Survey to be performed under my direction by:
<u> </u>		Graydon M. Adcock, Deputy
		Henry W. Herring
·		Witnessed by Art Mosher Theo Lilly, Jr. Wesley Warnamen 24.W./terring September 30, 1955.
· · · · · · · · · · · · · · · · · · ·		OREGON S

Book I

247

Page 2.