

CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY

Center One Quarter corner for Section 6, T. 2 N,  
R. 9W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 $\frac{1}{2}$ E

Set 1 $\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY C $\frac{1}{4}$  S6 1958 RS401," 34 inches in ground, and from which a:

10" Hemlock bears N35W 15.6 ft.; scribed C $\frac{1}{4}$  S6 BT.  
43" Fir bears S76E 59.0 ft.; scribed C $\frac{1}{4}$  S6 BT RS401.

Oregon State Board of Forestry metal location poster on 6" Spruce S67W 2.3 Ft. Set 4" x 4" x 60" white painted Cedar post 1.3' N.W. of pipe.

South One Sixteenth corner common to Sections 5 & 6,  
T. 2N, R. 9W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 $\frac{1}{2}$ E

Set 1 $\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY S1/16 S6 S5 1958 RS 401," 34 inches in ground, and from which a:

29" Hemlock bears S74E 12.7 ft.; scribed S 1/16 S5 BT RS401  
24" Hemlock bears S53W 12.0 ft.; scribed S 1/16 S6 BT


Oregon State Board of Forestry metal location poster on 29" Hemlock BT.  
Set 4" x 4" x 60" white painted Cedar post 1.0' S.W. of pipe.

Dated February 19, 1958

Established by



*Richard A. Morris*



Present and witnessed by Robert Sturm  
Harold Russell

Book I

322

181

322

322