CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY

West One Sixteenth corner common to Sections 10 and 15, T3N, R9W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 E

Set 12" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY W 1/16 S10 S15 1960 RS401", 33 inches in ground, and from which a:

17" Hemlock bears S24W 6.9 ft.; scribed W 1/16 S15 BT.
22" Hemlock bears N19E 25.0 ft.; scribed W 1/16 S10 BT RS401.

Oregon State Board of Forestry metal location poster on 24" Hemlock N65W 1.4 feet.
Set 4" x 4" x 72" white painted Fir post 1.0' S.E. of pipe.

Center One Quarter corner for Section 15, T3N, R9W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 1

Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY C 1/4 S15 1960 RS401", 35 inches in ground, in mound of stone, and from which a:

21" Hemlock bears N76W 27.3 ft.; scribed C 1/4 S15 BT RS401. 22" Hemlock bears S86 $\frac{1}{2}$ E 27.5 ft.; scribed C 1/4 S15 BT.

Oregon State Board of Forestry metal location poster on 21" Hemlock BT. Set 4" x 4" x 60" white painted Cedar post 1.0' S.W. of pipe.

Dated May 6, 1960

Established by

REGISTERED
OREGON
LAND SURVEYOR.

Richard A. Morris

401

Present and witnessed by R. Cop

G. Nylund