

CHAINS

ESTABLISHED CORNERS FOR STATE OF OREGON--DEPARTMENT OF FORESTRY
(See official plat)

Center South One-sixteenth corner for Section 24, T1N, R10W,
W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 1/2 E

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE
BOARD OF FORESTRY S 1/16 C---C S24 1962 RS401", 32 inches in ground,
and from which a:

18" Hemlock bears S41°W 4.6 ft.; scribed CS 1/16 S24 BT RS401.
24" Hemlock bears S40°E 7.9 ft.; scribed CS 1/16 S24 BT.

Set 4" x 4" x 56" white painted Cedar post 2.0 ft. NW of corner pipe.
Oregon State Forestry Department metal location poster on 24" Hemlock BT.

Established by Billy E. Davis under my direction.
Billy E. Davis, Transitman

Present and witnessed by A. Duncan

Southwest One-sixteenth corner for Section 24, T1N, R10W,
W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 1/2 E

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE
BOARD OF FORESTRY SW 1/16 S24 1962 RS401", 33 inches in ground, and
from which a:

36" Hemlock bears N56E 1.5 ft.; scribed SW 1/16 S24 BT RS401.
20" Hemlock bears S19 1/2 W 41.2 ft.; scribed SW 1/16 S24 BT.

Set 4" x 4" x 56" white painted Cedar post 1.0 ft. SE of corner pipe.
Oregon State Forestry Department metal location poster on 18" Hemlock
S84W 22.1 Ft.

Established by Allan E. Duncan under my direction.
Allan E. Duncan, Forestry Aide

Present and witnessed by D. Fletcher, C. Curl.

Dated December 21, 1962



Richard A. Morris
MAY 10, 1957
Richard A. Morris
401

Gen. S. 1/16 Cor
24-T.N. 10

SW 1/16 Cor
24-T.N. 10