

CHAINS

ESTABLISHED CORNER FOR STATE OF OREGON-DEPARTMENT OF FORESTRY
(See official plat)
Southeast One Sixteenth corner for Section 22, T2S, R9W,
W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 1/2 E

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE
BOARD OF FORESTRY SE 1/16 S22 1961 RS401", 34 inches in ground, and
from which a:

- 25" Hemlock bears S53 1/2 E 7.5 ft.; scribed SE 1/16 S22 BT.
- 28" Hemlock bears S76 W 13.0 ft.; scribed SE 1/16 S22 BT RS401.

Set 4" x 4" x 52" white painted Cedar post 1.0 ft. NW of corner pipe.
Oregon State Forestry Department metal location poster on 25" Hemlock BT.

Established by Harold J. Russell under my direction.
Harold J. Russell, Eng. Tech. I

Present and witnessed by G. Nylund

* * * * *

RE-ESTABLISHED CORNER FOR STATE OF OREGON-DEPARTMENT OF FORESTRY

One Quarter corner common to Sections 21 and 22, T2S, R9W, W.M.,
Tillamook County, Oregon.

No evidence of original corner found.

RE-ESTABLISHED

Var. 21 1/2 E

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE
BOARD OF FORESTRY 1/4 S21 S22 1961 RS401", 36 inches in ground, in
mound of rock, in pasture, and from which a:

- 96" Maple bears N18 1/2 W 192.6 ft.; scribed 1/4 S21 BT.
- 48" Maple bears S81 1/2 E 298.4 ft.; scribed 1/4 S22 BT RS401.

Center line Fawcett Creek Road, course N85W by S85E, bears South 60.4 ft.
NW corner of barn bears S15E 12.0 ft.

Set 4" x 4" x 52" white painted Cedar post 1.0 ft. SE of corner pipe.
Oregon State Forestry Department metal location poster on 48" Maple BT.

Dated November 9, 1961

Re-established by

Present and witnessed by G. Nylund
A. Duncan
H. Russell



Richard A. Morris
MAY 10, 1957
Richard A. Morris
401

SE 1/6 cor
22-2-S-9

1/4 cor
E. B...
21-2-S-9