

County Surveyor's Record, Tillamook County, Oregon

CHAINS

ESTABLISHED CORNERS FOR STATE OF OREGON-DEPARTMENT OF FORESTRY
(See official plat)

Center West One Sixteenth corner for Section 16, T3S, R8W,
W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 1/2 E

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE
BOARD OF FORESTRY W 1/16 C---C S16 1961 RS401", 33 inches in ground, and
from which a:

20" Fir bears N 77 1/2 W 70.0 ft.; scribed CW 1/16 S16 BT RS401.
36" Fir bears N 12 1/2 E 144.7 ft.; scribed CW 1/16 S16 BT.

Set 4" x 4" x 52" white painted Cedar post 1.0 ft. N.E. of corner pipe.
Oregon State Forestry Department metal location poster on 20" Fir BT.

Southwest One Sixteenth corner for Section 16, T3S, R8W,
W.M., Tillamook County, Oregon.

ESTABLISHED

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE
BOARD OF FORESTRY SW 1/16 S16 1961 RS401", 34 inches in ground, and from
which a:

24" Fir bears S10W 16.1 ft.; scribed SW 1/16 S16 BT RS401.
28" Fir bears S70E 8.7 ft.; scribed SW 1/16 S16 BT.

Set 4" x 4" x 52" white painted Cedar post 1.0 ft. S.E. of corner pipe.
Oregon State Forestry Department metal location poster on 19" Fir S57W
6.1 ft.

Dated January 22, 1962

Established by

REGISTERED
OREGON
LAND SURVEYOR

Richard A. Morris

MAY 10, 1957
Richard A. Morris
401

Present and witnessed by G. E. Nylund
A. Duncan

*Center West 1/16
16-3-18*

*S.W. 1/16
16-3-18*