

**TILLAMOOK COUNTY SURVEYORS OFFICE
COURT HOUSE, TILLAMOOK, OREGON 97141
SECTION CORNER, SECTIONS 22, 23, 26, 27, T.1N.,R.10W.,W.M.**

T1N R10W
S22 S23
+
S27 S26
1984
RS 1998

I FOUND A 1 1/2" IRON PIPE WITH A 3" OREGON STATE BOARD OF FORESTRY BRONZE CAP, (T.C.S. REWITNESS BOOK 6 AT PAGE 253), ENCASED IN AN IRREGULAR MASS OF CONCRETE. (REWITNESS CARD #52).

HISTORY OF FOUND MONUMENT

I FOUND THIS MONUMENT TO BE AS DESCRIBED IN SAID T.C.S. REWITNESS BOOK 6 AT PAGE 253 AND REWITNESS CARD #52. AND THE REFERENCES SET OR FOUND AT THAT TIME TO NOW BE AS FOLLOWS:

(G.L.O.) 16" HEMLOCK S.08°W 33 LINKS, REPORTED IN REWITNESS BOOK 6 AT PAGE 253 AS ROTTED REMAINS OF UPROOT; (FOUND ROTTED REMAINS, AT POSITION).

(G.L.O.) 24" SPRUCE S.48°E 20 LINKS, REPORTED IN REWITNESS BOOK 6 AT PAGE 253 AS ROTTED REMAINS OF UPROOT; (FOUND ROTTED REMAINS, AT POSITION).

(G.L.O.) 72" SPRUCE N.40°W 54 LINKS, REPORTED IN REWITNESS BOOK 6 AT PAGE 253 AS 76" STUMP, BADLY ROTTED, SCRIBES VISIBLE; (FOUND, NOW A 76" STUMP WITH ROTTED FACE, AT POSITION).

(G.L.O.) 32" SPRUCE N.31°E 44 LINKS, REPORTED IN REWITNESS BOOK 6 AT PAGE 253 AS BADLY ROTTED ROOT CROWN; (FOUND, NOW BADLY ROTTED ROOT CROWN, AT POSITION).

(UNRECORDED) 24" HEMLOCK S.51°E 4.0', REPORTED IN REWITNESS BOOK 6 AT PAGE 253 AS A 38" STUMP, CUT OFF BELOW FACE S.22°E. 5.0'; (FOUND, NOW 38" LOW CUT HEMLOCK STUMP S.22°E 5.0').

(BOOK 6 AT PAGE 253) 54" FIR STUMP N.23°E. 35.1' TO FACE; (FOUND, NOW A 7' TALL, 54" FIR STUMP, SCRIBING VISIBLE, AT POSITION, O.D.F. YELLOW METAL LOCATION POSTER ATTACHED).

(BOOK 6 AT PAGE 253) 22" HEMLOCK S.79°E. 120.5' TO FACE SCRIBED T1NR10W S26BT; (FOUND, NOW 26" HEMLOCK, FACE HEALED, AT POSITION. TREE IS FULL OF WOODPECKER HOLES).

(BOOK 6 AT PAGE 253) 14" ALDER S.09°E. 69.5' TO BARK SCRIBES T1NR10W S26BT; (FOUND, NOW 14" ALDER STUMP IN ROAD FILL, 12" HIGH, NO MARKS VISIBLE).

(REWITNESS CARD 52) *60" HAT SECTION POST SOUTH 1.5'; (FOUND, AT POSITION).

NEW ACCESSORIES

- *5" FIR N.53°W. 10.6' SCRIBED "BT".
- *6" FIR N.58°E. 8.92' SCRIBED "BT".
- *35" HEMLOCK S.6°W. 91.80' SCRIBED "T1NR10WS27BT".
- *24" HEMLOCK S.77°E. 113.94' SCRIBED "T1NR10WS26BTCS".

MEASUREMENTS TAKEN TO A BRASS WASHER NAILED TO THE FACE BETWEEN THE SCRIBED "B" AND "T".

*INDICATES TILLAMOOK COUNTY SURVEYORS YELLOW METAL LOCATION POSTER ATTACHED.

SURVEYS AND REWITNESSES OF RECORD

B-289	FEB. 1923	W. S. COATES C.S.	PE 967
B-123	UNKNOWN DATE	ROBERT WALKER	RS 150
B-419	12-31-59	RICHARD A. MORRIS	RS 401
A-1102	NOV. 1963	RICHARD A. MORRIS	RS 401
A-1212	FEB. 1965	JOHN L. CARLICH	RS 287
REWITNESS BOOK 6 PAGE 253	02-09-84	ANTHONY J. KLOSTERMAN	RS 1998


LOCATION OF MONUMENT

THIS CORNER IS LOCATED ± 60' NORTH OF A SPUR LOGGING ROAD ABOVE A HIGH CUT, IN A SALAL THICKET.

IN THE PRESENCE OF AL DVORAK AND DAN MCNUTT

APRIL 16, 1999

Title



REGISTERED
**PROFESSIONAL
LAND SURVEYOR**

Allan E. Duncan, C.S.
OREGON
JULY 14, 1987
ALLAN E. DUNCAN
793

EXPIRES 12-31-99