

REWITNESSED CORNER FOR OREGON DEPARTMENT OF FORESTRY
4907 Third St., Tillamook, Oregon 97141

One quarter corner common to Sections 15 and 16, T2N, R7W, W.M.,
Tillamook County, Oregon.

ORIGINAL by Henry Meldrum, September 11, 1891.

20"x12"x10" basalt stone with 1/4 on west face, 15" in ground;
now 6"x6"x7" with marks 1/ visible, on East edge of pipe.

- 18" Hemlock bears S67°E 41 lks.; now a 24"x3 foot high
badly rotted stump with axe work and portion of face
visible.
- 15" Hemlock bears S55°W 50 lks.; now a 23"x4 foot high
badly rotted stump, no face apparent.

NOTE: Distance to apparent face.

RESTORATION by Louis W. Amort RE2311, December 16, 1952 (Book
2, Page 240, Tillamook County Records).

1½"x36" galvanized iron pipe with 3" bronze cap, 30" in
ground, in mound of stone; in place at corner point.

- 60" Fir stump bears N76°E 15.4 ft.; now 5 foot high and
rotted with no face visible.
- 66" Fir snag bears S63°W 80.6 ft.; now a 6 foot high
rotted stump with no face visible.

REWITNESSED May 18, 2000


Var. 18½°E

From above pipe with marks "LS1998-2000" added a:

- 15" Fir bears N57°E 18.0 ft. to face; scribed 1/4S15BT.
- 13" Fir bears S68°E 19.05 ft. to face; scribed 1/4S15BT.
- 15" Hemlock bears S09½°W 38.8 ft. to face; scribed 1/4S16BT.
- 20" Fir bears N71°W 7.25 ft. to face; scribed 1/4S16BT.

Metal location poster on new BTs. Also 1952 tag on Amort's 60" Fir.
3/4" brass washer marked "LS1998" nailed to face of new BTs.
6 foot Carsonite post bears S30°E 2.2 ft.
Present and witnessed by Clifford R. Foster and Kevin A. Herkamp.

Rewitnessed by David B. Buchholz under my direction.
David B. Buchholz, LS2272



SURVEYED BY:

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Anthony J. Klosterman

OREGON
July 21, 1982
Anthony J. Klosterman
1998

4907 THIRD STREET
TILLAMOOK, OR 97141
EXPIRES JUNE 30, 2001