


TILLAMOOK COUNTY SURVEYORS OFFICE  
COURTHOUSE, TILLAMOOK, OREGON 97141

SECTION CORNER COMMON TO SECTIONS 7, 8, 17 AND 18, TOWNSHIP 2  
NORTH, RANGE 9 WEST, WILLAMETTE MERIDIAN, TILLAMOOK COUNTY,  
OREGON.

I FOUND A 3" DIAMETER OREGON STATE BOARD OF FORESTRY CAP ON A 1-1/2"  
DIAMETER IRON PIPE LEANING TO THE NORTH, STAMPED AS SHOWN HEREON.  
I PLUMBED THE IRON PIPE AND BRASS DISK AND PLACED 120 POUNDS OF  
CONCRETE INSIDE OF A 12" DIAMETER PLASTIC CYLINDER AROUND THE  
EXISTING MONUMENT.



---

HISTORY OF FOUND MONUMENT

THIS CORNER WAS ORIGINALLY SET BY THE GENERAL LAND OFFICE BY G.L.O. SURVEYOR HENRY MELDRUM IN 1884. THE CORNER WAS THEN RESTORED BY ARNOLD G. GIBSON, L.S. 359, IN 1956 FOR THE OREGON STATE BOARD OF FORESTRY. THERE WERE FOUR BEARING TREES SET AS ACCESSORIES TO THE ORIGINAL CORNER POST SET IN 1884. THREE OF THE ORIGINAL BEARING TREES ARE NOW GONE. A ROTTEN SPRUCE STUMP WAS FOUND AT RECORD POSITION IN A CREEK BOTTOM WITH NO VISIBLE MARKINGS. THIS STUMP IS THE REMAINS OF THE ORIGINAL 16" DIAMETER SPRUCE TREE SET BY THE GLO BEARING SOUTH 45° WEST 44 LINKS. GIBSON FOUND A 36" DIAMETER STUB 10' HIGH WITH SCRIBES "T2N R9W S" VISIBLE.

THE MONUMENT WAS FOUND AS DESCRIBED IN REWITNESS BOOK 1, PAGE 264 AND THE ACCESSORIES FOUND AND/OR SET AT THAT TIME TO NOW BE AS FOLLOWS:

REWITNESS BOOK 1, PAGE 264 – SET A 6" DIAMETER SPRUCE TREE WHICH BEARS SOUTH 1° WEST 16.7 FT. SCRIBED "T2N R9W S18 BT RS 359"; 06-29-06 – FOUND A 40" DIAMETER SPRUCE TREE WITH TWO OREGON STATE FORESTRY DEPARTMENT METAL LOCATION POSTERS WITH A HEALED FACE AT RECORD POSITION.

REWITNESS BOOK 1, PAGE 264 – SET A 34" DIAMETER ALDER TREE WHICH BEARS NORTH 58° WEST 36.9 FT. BARK SCRIBED "T2N R9W S7 BT"; 06-29-06 – FOUND A 40" DIAMETER ALDER TREE WITH VISIBLE BARK SCRIBING AT RECORD POSITION.

REWITNESS BOOK 1, PAGE 264 - SET AN 18" DIAMETER ALDER TREE BARK SCRIBED "T2N R9W S17 BT"; 06-29-06 – BEARING TREE IS NOW GONE.

REWITNESS BOOK 1, PAGE 264 – SET A 12" DIAMETER FIR TREE WHICH BEARS NORTH 25 1/2° EAST 121.7 FT. SCRIBED "T2N R9W S8 BT"; 04-07-06 – SEARCHED FOR, NOT FOUND.

REWITNESS BOOK 1, PAGE 264 - OREGON STATE FORESTRY DEPARTMENT METAL LOCATION POSTER ON 6" DIAMETER SPRUCE BEARING TREE; 06-29-06 – FOUND AT RECORD POSITION.

REWITNESS BOOK 1, PAGE 264 - SET A 4" X 4" X 72" WHITE PAINTED CEDAR POST 1.0 FEET NE OF PIPE; 04-07-06 - FOUND 4" X 4" WHITE PAINTED CEDAR POST WITH BOTTOM ROTTED OFF LYING ON THE GROUND NEXT TO THE MONUMENT.

---

**SURVEYS AND REWITNESSES OF RECORD**

GLO Contract #500, by Henry Meldrum, 1884, BLM Volume: OR-R0310 Page: 0272.0  
GLO Book 1 AND 2N, Page 78, Tillamook County Survey Records.  
Rewitness Book 1, Page 264, 1954, Arnold G. Gibson, L.S. 359, Tillamook County Survey Records.

---

**NEW ACCESSORIES**

SET A NAIL AND BRASS WASHER STAMPED "T.C. SURV" IN AN EXISTING 40" DIAMETER SPRUCE BEARING TREE WHICH BEARS SOUTH 1° WEST A DISTANCE OF 15.49'.

\*26" DIAMETER SPRUCE TREE LOCATED ALONG THE EASTERLY EDGE OF A LOGGING ROAD WHICH BEARS SOUTH 76° EAST 73.59' SCRIBED "T2NR9WS17BT". DISTANCE WAS MEASURED TO A NAIL AND BRASS WASHER STAMPED "T.C. SURV" NAILED TO THE FACE BETWEEN THE SCRIBED 'B' & 'T'.

\*SET AN 84" LONG HAT SECTION POST NORTH 3.0' FROM THE MONUMENT.

BASIS OF BEARINGS FOR BEARING TREES IS MAGNETIC.

\* INDICATES TILLAMOOK COUNTY YELLOW METAL LOCATION POSTER ATTACHED.

---

**LOCATION OF MONUMENT**

THIS SECTION CORNER IS LOCATED APPROXIMATELY 40' NORTHWESTERLY OF A LOGGING ROAD ON A STEEP SOUTHERLY FACING SLOPE.

IN THE PRESENCE OF, AND REWITNESSED BY DANNY R. MCNUTT, TILLAMOOK COUNTY SURVEYOR, JOE JENSEN, SURVEY SUPERVISOR, AND AL DVORAK, SURVEY TECHNICIAN, TILLAMOOK COUNTY SURVEYOR'S OFFICE.

---

JUNE 29, 2006

TITLE:

