

CORNER INVESTIGATION REPORT

FS INDEX ID: N-25 & N-1

CORNER: SECTION GCDB ID: 700400 & 100400 DATE: 01/04/2018
TOWNSHIP: 3S STATE: OREGON
RANGE: 10W & 9W COUNTY: TILLAMOOK
SECTION: 13 & 24, 18 & 19 FOREST: SIUSLAW
MERIDIAN: WILLAMETTE DISTRICT: HEBO
NFSL PROPERTY BOUNDARY CORNER?: YES NO
LINE(S) POSTED: NORTH - 1979 SOUTH - 1979
MAINTAINED: NORTH - 2017 SOUTH - 2017
GUARD POST(S): NORTH - 1.4 FT

HISTORY OF VISITATIONS:

- (1)1880 - S.G. CAUDEL, GLO SURVEY
- (2)1882 - W.P. WRIGHT, GLO RESURVEY
- (3)1969 - H.J. RUSSELL, CSF# A-1747
- (4)1979 - L.D. BISHOP, CSF# B-830
- (5)1989 - D.K. FERGUSON, CSF# B-1366

CORNER HISTORY:

- (1) ESTABLISHED CORNER, SET STONE (10x6x6) & BUILT STONE MOUND PER EXTERIOR BOUNDARY NOTES, CALLS FOR POST IN SUBDIVISION OF 3S 9W.
- (2) FOUND POST & 4 BT'S AT CORNER POSITION NOT DESCRIBED IN 1880 NOTES, NO MENTION OF STONE MOUND.
- (3) SEARCHED FOR, COMPUTES PROPORTIONED POSITION.
- (4) RE-ESTABLISHED CORNER, SET ALUMINUM PIPE/CAP & 4 BT'S.
- (5) FOUND ALUMINUM PIPE/CAP & 4 BT'S, SET ALUMINUM PIPE/CAP RM & 3 BT'S.

MONUMENT FOUND/SET:

FOUND A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP, PROJECTING 4" ABOVE THE GROUND.

RECORD CORNER ACCESSORIES:

- NO TRACE FOUND OF A (1)STONE MOUND
- NO TRACE FOUND OF A (2)6" VINE MAPLE
- NO TRACE FOUND OF A (2)7" VINE MAPLE
- NO TRACE FOUND OF A (2)6" VINE MAPLE
- NO TRACE FOUND OF A (2)4" VINE MAPLE
- NO TRACE FOUND OF A (4)16" HEM, (5)14" BY 8' SNAG WITH SCRIBES VISIBLE.
- A 60" SPRUCE STUMP WITH SCRIBES VISIBLE ON PART. HEALED DOUBLE BLAZE.
- A ROOT HOLE, FORMALLY A (4)14" FIR
- AN INDETERMINATE SIZE STRUCE STUMP WITH NO MARKS VISIBLE.
- A 20" HEMLOCK WITH A HEALED DOUBLE BLAZE.
- A 9" FIR WITH A HEALED DOUBLE BLAZE.
- A 7" FIR WITH A HEALED DOUBLE BLAZE.
- A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP FOR RM, PROJECTING 3" ABOVE THE GROUND & MARKED AS DESCRIBED IN (5).

NEW CORNER ACCESSORIES:

NO NEW ACCESSORIES ESTABLISHED.

CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREAST HEIGHT.

NFSL LINES BEAR: (5)N0°26'52"E - 1302.21 FT & (4)S0°25'28"W - 1269.92 FT

GEODETTIC COORDINATES:

LATITUDE: N 45° 18' 07.612"
 LONGITUDE: W 123° 50' 38.451"
 ELLIPSOID HEIGHT:

DATUM: WGS 84

SOURCE: USGS QUAD MAP, FOR NAVIGATION TO CORNER.

DATE OF INVESTIGATION: 12/12/2017

REPORT BY: JONATHAN B. DREW II, PLS#89396, CFedS#1664

FIELD CREW: ANDREW HILLMAN, USFS SURVEY TECH
 KYRK BARRON, USFS FIRE F.E.O.

DOCUMENTS ON FILE AT:

WILLAMETTE NATIONAL FOREST
 3106 PIERCE PARKWAY, STE D
 SPRINGFIELD, OREGON 97477

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

Jonathan B. Drew II

OREGON
 DECEMBER 3, 2014
 JONATHAN B. DREW II
 89396

EXPIRES: 12/31/2019

RECORD MEASUREMENTS:

- (1)ALONGSIDE
- (2)N81°W - 1.98 FT
- (2)S71°W - 12.54 FT
- (2)N52°E - 14.52 FT
- (2)S10°E - 1.98 FT
- (4,5)N2°E - 31.5 FT
- (4,5)S65°E - 12.4 FT
- (4)N64°W - 29.0 FT, (5)N58°W
- (4,5)S54°W - 34.3 FT
- (5)S16°30'E - 7.6 FT
- (5)S59°30'W - 17.5 FT
- (5)N63°W - 11.6 FT
- (5)N0°23'E - 51.1 FT

METHOD OF MEASUREMENT:

NO NEW MESUREMENTS TAKEN,
 FILED AS CONDITION REPORT.

CAP DIAGRAM:



THIS DOCUMENT FILED IN CS OFFICE: YES
OTHER DOCUMENT FILED WITH CS: NONE

