

CORNER INVESTIGATION REPORT

FS INDEX ID: D-21

CORNER: SOUTH 1/16 **GCDB ID:** 620600 **DATE:** 12/3/2021
TOWNSHIP: 3 S **STATE:** OREGON
RANGE: 9 W **COUNTY:** TILLAMOOK
SECTION: 1 & 2 **FOREST:** SIUSLAW
MERIDIAN: WILLAMETTE **DISTRICT:** HEBO

HISTORY OF VISITATIONS:

(1) 1991 - L. BISHOP, CS# B-1510

NFSL PROPERTY BOUNDARY CORNER?: YES NO


LINE(S) POSTED: NORTH - 1991 WEST - 1991

MAINTAINED: NORTH - 2019 WEST - 2019


GUARD POST(S): NORTH - 3 FT WEST - 3.4 FT

CORNER HISTORY:

(1) ESTABLISHED CORNER BY SURVEY, SET ALUMINUM PIPE/CAP WITH 2 BT'S.



Jonathan B. Drew II



EXPIRES: 6/30/2021

RECORD MEASUREMENTS:

(1)N6°W - 8.1 FT

(1)N22°30'E - 22.0 FT

MONUMENT FOUND/SET:

FOUND A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP, PROJECTING 6 INCHES ABOVE THE GROUND. NOTE: CAP IS LOOSE ON PIPE.

RECORD CORNER ACCESSORIES:

A 15" FIR WITH A HEALED SINGLE BLAZE.

A 15" FIR WITH A HEALED SINGLE BLAZE.

NEW CORNER ACCESSORIES:

NO NEW ACCESSORIES ADDED.

METHOD OF MEASUREMENT:

NO NEW MEASUREMENTS TAKEN,
FILED AS CONDITION REPORT.

CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S. BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREST HEIGHT.

NFSL LINES BEAR: (1)N2°12'33"E - 1349.46 FT & (2)S89°30'48"W - 1406.04 FT

GEODETIC COORDINATES:

LATITUDE: N 45° 20' 2.606"

LONGITUDE: W 123° 44' 32.033"

ELLIPSOID HEIGHT: ~ 1542 FT

DATUM: WGS 84

SOURCE: CONSUMER GRADE GPS, FOR NAVIGATION TO THE CORNER.

DATE OF INVESTIGATION: 6/4/2019

REPORT BY: JONATHAN B. DREW II, PLS# 89396

ASSISTED BY: ANDREW HILLMAN, USFS SURVEY TECH
CHRISTIAN HUNTER, USFS SURVEYOR TRAINEE

DOCUMENTS ON FILE AT:

WILLAMETTE NATIONAL FOREST
3106 PIERCE PARKWAY, STE D
SPRINGFIELD, OREGON 97477

THIS DOCUMENT FILED IN CS OFFICE: YES

OTHER DOCUMENT FILED WITH CS: NONE

CAP DIAGRAM:

