



CORNER INVESTIGATION REPORT

FS INDEX ID: U-23


CORNER: CENTER SOUTH 1/16 **GCDB ID:** 640220 **DATE:** 6/11/2018
TOWNSHIP: 3S **STATE:** OREGON
RANGE: 8W **COUNTY:** TILLAMOOK
SECTION: 25 **FOREST:** SIUSLAW
MERIDIAN: WILLAMETTE **DISTRICT:** HEBO
NFSL PROPERTY BOUNDARY CORNER?: YES NO
LINE(S) POSTED: EAST - 1985 WEST - 1985
MAINTAINED: EAST - NONE WEST - 2017
GUARD POST(S): EAST ~ 3 FT WEST ~ 3 FT

HISTORY OF VISITATIONS:


(1)1985 - L. BISHOP, CSF# B-1196

CORNER HISTORY:

(1) ESTABLISHED CORNER BY SURVEY, SET ALUMINUM PIPE/CAP FOR CORNER & RM, MARKED 1 BT.



Jonathan B. Drew II



EXPIRES: 12/31/2019

RECORD MEASUREMENTS:

MONUMENT FOUND/SET:

FOUND A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP, PROJECTING 2" ABOVE THE GROUND.

RECORD CORNER ACCESSORIES:

A 27" ALDER WITH BARK SCRIBE VISIBLE. (1)S56°W - 27.1 FT
 A 2-1/2" ALUMINUM PIPE WITH 3-1/4" ALUMINUM CAP RM, PROJECTING 4" ABOVE THE GROUND, MARKED AS DESCRIBED IN (1). (1)N80°57'W - 57.4 FT

NEW CORNER ACCESSORIES:

NO NEW ACCESSORIES ESTABLISHED.

METHOD OF MEASUREMENT:

NO NEW MEASUREMENTS TAKEN, FILED AS CONDITION REPORT.

CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREAST HEIGHT.

NFSL LINES BEAR: (1)N89°12'44"W - 1277.19 FT & (1)S88°59'05"E - 1281.70 FT

GEODETIC COORDINATES:

LATITUDE: N 45° 16' 37.740"
 LONGITUDE: W 123° 36' 59.952"
 ELLIPSOID HEIGHT:

DOCUMENTS ON FILE AT:

WILLAMETTE NATIONAL FOREST
 3106 PIERCE PARKWAY, STE D
 SPRINGFIELD, OREGON 97477

DATUM: WGS 84

SOURCE: USGS QUAD MAP, FOR NAVIGATION TO CORNER.

DATE OF INVESTIGATION: 11/14/2017

REPORT BY: JONATHAN B. DREW II, PLS #89396, CFedS #1664

FIELD CREW: JACOB HUNT, USFS SURVEY TECH.
 ANDREW HILLMAN, USFS SURVEY TECH

THIS DOCUMENT FILED IN CS OFFICE: YES
OTHER DOCUMENT FILED WITH CS: RECORD OF SURVEY FILED SEPARATELY

