



CORNER INVESTIGATION REPORT

FS INDEX ID: V-17

CORNER: SECTION GCDB ID: 500200 DATE: 6/11/2018
TOWNSHIP: 3S STATE: OREGON
RANGE: 8W COUNTY: TILLAMOOK
SECTION: 26, 27, 34 & 35 FOREST: SIUSLAW
MERIDIAN: WILLAMETTE DISTRICT: HEBO
NFSL PROPERTY BOUNDARY CORNER?: YES NO
LINE(S) POSTED: NORTH - 1985 SOUTH - 1985
MAINTAINED: NORTH - 2017 SOUTH - 2017
GUARD POST(S): NORTH ~ 4 FT SOUTH ~ 4 FT

HISTORY OF VISITATIONS:
 (1)1884 - H. MELDRUM, GLO SURVEY
 (2)1963 - L. WHITMORE, RW3/167 & RW2/560
 (3)1969 - H. RUSSELL, CSF# B-598 & RW5/35
 (4)1971 - K.M. WIGHTMAN, CSF# B-607
 (5)1985 - L. BISHOP, CSF# B-1192, B-1193 & B-1195
 (6)2013 - T. JONES, CSF# B-3588

CORNER HISTORY:

- (1) ESTABLISHED CORNER, SET POST & 4 BT'S.
- (2) FOUND 4 BT'S. SET POST & 4 NEW BT'S.
- (3) FOUND POST SET IN 1963 OUT OF POSITION & 8 BT'S. SET GALVANIZED IRON PIPE/BRONZE CAP IN A HOLE CHOPPED THROUGH A 22" HOLLOW LOG.
- (4) FOUND IRON PIPE/BRASS CAP & 7 BT'S.
- (5) FOUND IRON PIPE/BRASS CAP & 6 BT'S. SETS ALUMINUM PIPE/CAP & 1 NEW BT
- (6) MAP NOTES CORNER FOUND, NOT TIED

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Jonathan B. Drew II
 OREGON
 DECEMBER 3, 2014
 JONATHAN B. DREW II
 89396

MONUMENT FOUND/SET:

FOUND A 2" GALVANIZED IRON PIPE WITH A 3" BRASS CAP, PROJECTING 15" ABOVE THE GROUND.

EXPIRES: 12/31/2019

RECORD CORNER ACCESSORIES:

A 43" ROTTED FIR STUMP WITH NO MARKS VISIBLE.
 AN INDETERMINATE SIZE ROTTED FIR STUB WITH NO MARKS VISIBLE.
 NO TRACE FOUND OF A (1)34" FIR, (3)40" STUB, (4)SNAG
 AN INDETERMINATE SIZE ROTTED FIR STUMP WITH NO MARKS VISIBLE.
 NO TRACE FOUND OF A (2)18" ALDER, (3)21", (4)24", (5)SAWN STUMP
 A 24" FIR WITH A HEALED SINGLE BLAZE.
 A 46" FIR WITH A HEALED SINGLE BLAZE. NOTE: HAND COMPASS AGREES WITH S16°W BEARING NOT S46°W PER (5).
 A 20" FIR STUMP WITH A HEALED SINGLE BLAZE.
 A 20" FIR WITH A HEALED SINGLE BLAZE.
 A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP FOR RM, PROJECTING 5" ABOVE THE GROUND, MARKED AS DESCRIBED IN (5).

RECORD MEASUREMENTS:
 (1,2,3,5)N26°30'W - 21.78 FT, (4)24.0 FT
 (1,2,3,5)S29°W - 42.24 FT, (4)S30°W - 41.6 FT
 NOTE: SLOPE DIST PER (5).
 (1,2,3)S45°E - 58.08 FT, (4)57.5 FT
 (1)N67°30'E - 54.12 FT, (2,3)34.3 FT
 (2,3)N18°E - 31.68 FT, (4)32.7 FT, (5)32.9 FT
 (2,3)N16°W - 34.98 FT, (4,5)N14°W - 36.4 FT
 (2,3)S13°W - 25.74 FT, (4)S16°W - 24.5 FT,
 (5)S46°W
 (2,3)S10°E - 52.8 FT, (4,5)S9°E - 50.8 FT
 (5)S31°15'E - 52.1 FT
 (5)N20°42'50"E - 49.6 FT

NEW CORNER ACCESSORIES:

NO NEW ACCESSORIES ESTABLISHED.

METHOD OF MEASUREMENT:

NO NEW MEASUREMENTS TAKEN, FILED AS CONDITION REPORT.

CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREST HEIGHT.

NFSL LINES BEAR: (5)S1°32'57"E - 2772.03 FT & (5)N1°41'53"W - 2551.92 FT.

GEODETIC COORDINATES:

LATITUDE: N 45° 16' 25.413"
LONGITUDE: W 123° 38' 46.141"
ELLIPSOID HEIGHT:
DATUM: WGS 84

DOCUMENTS ON FILE AT:

WILLAMETTE NATIONAL FOREST
 3106 PIERCE PARKWAY, STE D
 SPRINGFIELD, OREGON 97477

SOURCE: USGS QUAD MAP, FOR NAVIGATION TO CORNER

DATE OF INVESTIGATION: 11/21/2017

REPORT BY: JONATHAN B. DREW II, PLS #89396, CFedS #1664

FIELD CREW: JACOB HUNT, USFS SURVEY TECH
 ANDREW HILLMAN, USFS SURVEY TECH

THIS DOCUMENT FILED IN CS OFFICE: YES
OTHER DOCUMENT FILED WITH CS: RECORD OF SURVEY FILED SEPARATELY

CAP DIAGRAM:

