



**CORNER INVESTIGATION REPORT**

FS INDEX ID: X-23

**CORNER:** CENTER 1/4                      **GCDB ID:** 640140                      **DATE:** 6/11/2018  
**TOWNSHIP:** 3S                                      **STATE:** OREGON  
**RANGE:** 8W                                          **COUNTY:** TILLAMOOK  
**SECTION:** 36                                        **FOREST:** SIUSLAW  
**MERIDIAN:** WILLAMETTE                      **DISTRICT:** HEBO  
**NEFL PROPERTY BOUNDARY CORNER?:**  YES  NO  
**LINE(S) POSTED:** NORTH - 1985      EAST - 1985  
**MAINTAINED:** NORTH - 2017      EAST - NONE  
**GUARD POST(S):** NORTH - 4 FT      EAST - 4.5 FT

**HISTORY OF VISITATIONS:**

- (1)1967 - B. UDELL, CSF# A-1405 & RW3/65
- (2)1969 - H. RUSSELL, CSF# B-598
- (3)1985 - L. BISHOP, CSF# B-1191

**CORNER HISTORY:**

- (1) ESTABLISHED CORNER BY SURVEY, SET PIPE/BRASS CAP & 2 BT'S.
- (2) FOUND IRON PIPE/BRASS CAP ESTABLISHED BY UDELL.
- (3) FOUND MONUMENT OUT OF POSITION, REESTABLISHED CORNER BY SURVEY, SET ALUMINUM PIPE/ALUMINUM CAP AT CORNER AND FOR REFERENCE MONUMENT & MARKS 1 NEW BT STUMP.

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

*Jonathan B. Drew II*

**OREGON**  
DECEMBER 3, 2014  
**JONATHAN B. DREW II**  
89396

**MONUMENT FOUND/SET:**

FOUND A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP, BURIED 4" IN FOREST DUFF.

EXPIRES: 12/31/2019

**RECORD CORNER ACCESSORIES:**

- A 2-1/2" IRON PIPE WITH A 2-1/2" BRASS CAP FOR REFERENCE MONUMENT, PROJECTING 12" ABOVE THE GROUND. MARKED AS DESCRIBED IN (3).
- A 24" FIR SAWN STUMP, NO MARKS ON A PARTIALLY HEALED SINGLE BLAZE.
- ROTTED REMAINS OF AN INDETERMINATE SIZE FIR STUMP, NO MARKS VISIBLE.
- NO TRACE FOUND OF A (3)RR SPIKE IN TOP OF 40" SCRIBED FIR STUMP
- A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP FOR REFERENCE MONUMENT, PROJECTING 8" ABOVE THE GROUND. MARKED AS DESCRIBED IN (3).

**RECORD MEASUREMENTS:**

- (3)N1°11'48"E - 94.58 FT
- (1)S52°W - 23.0 FT (FROM IRON PIPE RM)
- (1)N78°E - 1.8 FT (FROM IRON PIPE RM)
- (3)S45°W - 16.95 FT
- (3)N26°44'E - 46.1 FT

**NEW CORNER ACCESSORIES:**

NO NEW ACCESSORIES ESTABLISHED.

**METHOD OF MEASUREMENT:**

NO NEW MEASUREMENTS TAKEN, FILED AS CONDITION REPORT.

**CORNER MAINTENANCE/OTHER INFO:**

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREST HEIGHT.

NFSL LINES BEAR: (3)N88°03'22"E - 1280.28 FT & (3)N00°04'55"W - 2712.72 FT

**GEODETIC COORDINATES:**

**LATITUDE:** N 45° 15' 58.669"  
**LONGITUDE:** W 123° 36' 59.998"  
**ELLIPSOID HEIGHT:** ~1480 FT  
**DATUM:** WGS 84

**DOCUMENTS ON FILE AT:**

WILLAMETTE NATIONAL FOREST  
 3106 PIERCE PARKWAY, STE D  
 SPRINGFIELD, OREGON 97477

SOURCE: CONSUMER GRADE GPS, FOR NAVIGATION TO CORNER

**DATE OF INVESTIGATION:** 11/28/2017

**REPORT BY:** JONATHAN B. DREW II, PLS #89396, CFedS #1664

**FIELD CREW:** JACOB HUNT, USFS SURVEY TECH  
 ANDREW HILLMAN, USFS SURVEY TECH

**THIS DOCUMENT FILED IN CS OFFICE:** YES

**OTHER DOCUMENT FILED WITH CS:** RECORD OF SURVEY FILED SEPARATELY

**CAP DIAGRAM:**

