

CORNER INVESTIGATION REPORT

FS INDEX ID: V-5

CORNER: SECTION GCDB ID: 200200 DATE: 5/3/2018

TOWNSHIP: 3S STATE: OREGON

RANGE: 7W COUNTY: TILLAMOOK

SECTION: 29, 30, 31 & 32 FOREST: SIUSLAW

MERIDIAN: WILLAMETTE DISTRICT: HEBO

NFSL PROPERTY BOUNDARY CORNER?: YES NO

LINE(S) POSTED: SOUTH - 2018 EAST - 2018

MAINTAINED:

GUARD POST(S): SOUTH - 3 FT EAST - 1.2 FT

CORNER HISTORY:

- (1) ESTABLISHED CORNER, SET POST, 3 BT'S & DUG A PIT.
- (2) NO RECORD, LIKELY FOUND 3 BT'S & SET CROOKED WOODEN POST.
- (3) FOUND CROOKED WOODEN POST, NOT ORIGINAL, & 3-4 BT'S. SET IRON PIPE/BRASS CAP & MARKED 1 NEW BT.
- (4) FOUND IRON PIPE/BRASS CAP & 4 BT'S, MARKED 2 NEW BT'S.
- (5) FOUND IRON PIPE/BRASS CAP & 6 BT'S, SET R/R SPIKE IN STUMP FOR RM.

MONUMENT FOUND/SET:

FOUND A 2-1/2" GALVANIZED IRON PIPE WITH A 3-1/4" BRASS CAP, PROJECTING 7" ABOVE THE GROUND.

RECORD CORNER ACCESSORIES:

A 28" ALDER BEARS, S77°15'E - 48.2 FT, WITH A HEALED BLAZE.

A 44" FIR STUMP BEARS S88°45'W - 53.2 FT.

NO TRACE FOUND OF A (1)8" ALDER

NO TRACE FOUND OF A (1)PIT 18"x18"x12"DEEP

A 52" FIR BEARS, N62°30'E - 74.4 FT, WITH A HEALED BLAZE.

A 21" FIR BEARS, S21°W - 72.8 FT, WITH A HEALED BLAZE.

A 43" FIR STUMP BEARS N43°29'W - 62.3 FT TO RR SPIKE IN CENTER TOP.

NEW CORNER ACCESSORIES:

A 20" ALDER BEARS, N69°30'W - 62.7 FT, MARKED T3SR7WS30""BT"

NEW BT MARKED ON A DOUBLE BLAZE & INCLUDES A 3/4" BRASS WASHER MARKED "ORPLS89396" NAILED FLUSH BETWEEN THE "B" & "T" SCRIBES.

CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREAST HEIGHT.

NFSL LINES BEAR: S0°41'42"W - 2608.97 FT & S88°41'W - 2620.33 FT

GEODETTIC COORDINATES:

LATITUDE: N 45° 16' 23.881"

LONGITUDE: W 123° 35' 10.364"

ELLIPSOID HEIGHT:

DATUM: WGS 84

SOURCE: USGS QUAD MAP, FOR NAVIGATION TO CORNER.

DATE OF INVESTIGATION: 2/5/2018

REPORT BY: JONATHAN B. DREW II, PLS# 89396, CFed# 1664

FIELD CREW: WAVERLY K. HAYNER, BLM SURVEY TECH
LOWELL PEARSON, BLM SURVEY TECH

HISTORY OF VISITATIONS:

- (1) 1894 - F. SHARP, GLO SURVEY
- (2) ??? - UNKNOWN SURVEYOR & YEAR
- (3) 1962 - N. NEWTON, BLM RESURVEY, RW1/497 & 500
- (4) 1984 - F. TUERS, BLM RESURVEY, RW6/268 & F40-354
- (5) 1985 - L. BISHOP, CSF# B-1194

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Jonathan B. Drew II

OREGON
DECEMBER 3, 2014
JONATHAN B. DREW II
89396

EXPIRES: 12/31/2019

RECORD MEASUREMENTS:

(1)S74°E - 48.84 FT, (3)46.2 FT,

(4)S76°45'E - 47.85 FT, (5)47.8 FT

(1)S86°W-57.42 FT, (3,4)S89°W-53.46 FT

(1)N51°15'W - 90.42 FT, (3)N51°30'W,

(4)N51°15'W, (5)87.1 FT

(1)NORTHEAST - 5.5 FT

(3)N63°E - 75.24 FT, (4)73.59 FT, (5)73.6 FT

(4,5)S21°15'W - 72.6 FT

(4)N43°30'W - 62.04 FT, (5)62.0 FT,

(5)62.5 FT TO RR SPIKE IN TOP

METHOD OF MEASUREMENT:

TRIMBLE S7 TOTAL STATION, SEE RECORD OF SURVEY FOR BASIS OF BEARINGS & OTHER INFORMATION.

BT BEARINGS TO CENTER, DISTANCES TO AN ALUMINUM NAIL SET AT SIDE CENTER.

CAP DIAGRAM:



THIS DOCUMENT FILED IN CS OFFICE: YES

OTHER DOCUMENT FILED WITH CS: RECORD OF SURVEY

