

### CORNER INVESTIGATION REPORT

FS INDEX ID: P-23

CORNER: CENTER 1/4                      GCDB ID: 640340                      DATE: 5/1/2018  
TOWNSHIP: 3S                              STATE: OREGON  
RANGE: 8W                                COUNTY: TILLAMOOK  
SECTION: 24                               FOREST: SIUSLAW  
MERIDIAN: WILLAMETTE              DISTRICT: HEBO

HISTORY OF VISITATIONS:


(1)1964 - L. WHITMORE, PER BT TAGS

NFSL PROPERTY BOUNDARY CORNER?:     YES  NO

LINE(S) POSTED:  
MAINTAINED:  
GUARD POST(S):  
CORNER HISTORY:

(1) NO RECORD LOCATED, ESTABLISHED 'WORKING' CORNER, MARKS 2 BT'S.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR



OREGON  
DECEMBER 3, 2014  
JONATHAN B. DREW II  
89396

MONUMENT FOUND/SET:

NO MONUMENT FOUND RELATED TO 1964 'WORKING' CORNER & BT'S, AT INTERSECTION OF EAST-WEST AND NORTH-SOUTH CENTERLINES OF SECTION 24 SET 2-1/2"x28" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP, PROJECTING 4" ABOVE THE GROUND.

RECORD CORNER ACCESSORIES:

AN INDETERMINATE SIZE FIR STUB BEARS, S16°57'W - 34.6 FT, WITH AX WORK VISIBLE & BT TAG PRESENT.                      (1)N32°30'E - 11.65 FT  
 A 38" FIR SNAG BEARS, S16°25'E - 12.3 FT, WITH A HEALED DOUBLE BLAZE & BT TAG PRESENT.                      (1)S37°W - 14.0 FT

EXPIRES: 12/31/2019  
RECORD MEASUREMENTS:  
 PER FOUND BEARING TREE TAGS

NEW CORNER ACCESSORIES:

A 20" CEDAR BEARS, N5°54'E - 45.5 FT, MARKED "X"BT".  
 A 8" HEMLOCK BEARS, N16°04'W - 57.7 FT, MARKED "C1/4S24"BT".  
 A 26" CEDAR BEARS, S00°10'W - 41.8 FT, MARKED "C1/4S24"BT".  
 A 38" FIR BEARS, S70°56'W - 25.4 FT, MARKED "C1/4S24"BT".  
 ALL NEW BT'S MARKED ON A DOUBLE BLAZE & INCLUDE A 3/4" BRASS WASHER MARKED "OR PLS 89396" NAILED BETWEEN "B"&"T" SCRIBES.


METHOD OF MEASUREMENT:

TRIMBLE S7 TOTAL STATION, SEE RECORD OF SURVEY FOR BASIS OF BEARINGS & OTHER INFORMATION.  
 BT BEARINGS TO CENTER, DISTANCES TO AN ALUMINUM NAIL SET AT SIDE CENTER.

CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREAST HEIGHT.

CAP DIAGRAM:



GEODETIC COORDINATES:

LATITUDE: N 45° 17' 41.94253"  
 LONGITUDE: W 123° 37' 00.59832"  
 ELLIPSOID HEIGHT: ~1655 FT  
 DATUM: NAD83(2011), EPOCH:2010.0000

DOCUMENTS ON FILE AT:

WILLAMETTE NATIONAL FOREST  
 3106 PIERCE PARKWAY, STE D  
 SPRINGFIELD, OREGON 97477

SOURCE: CONSTRAINED LEAST SQUARES NETWORK ADJUSTMENT, SEE MAP.

DATE OF INVESTIGATION: 2/13/2018

REPORT BY: JONATHAN B. DERW II, PLS 89396, CFedS#1664

FIELD CREW: JONATHAN B. DREW II, PLS#89396, CFedS# 1664  
 WAVERLY K. HAYNER, BLM SURVEY TECH  
 GENE DAGUERRE, BLM SURVEY TECH  
 JACOB HUNT, USFS SURVEY TECH

THIS DOCUMENT FILED IN CS OFFICE: YES  
OTHER DOCUMENT FILED WITH CS: RECORD OF SURVEY

